




DESIGN <i>CP</i>	DRAWN BY <i>CP</i>	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
CHECKED <i>A</i>	APPROVED <i>A</i>	DRAWING NO. D6005	REV. A SHEET 1 OF 1
DATE 00.11.17		TITLE CROSSTUBE MATERIAL	SCALE 1:1
A	00.11.17	NEW ISSUE	

SPECIFICATION CONTROL DRAWING

RELEASED
00.11.24 *A*



NOTES

- 1) D6005-XXX CROSSTUBE
LENGTH

WHERE XXX IS LENGTH IN INCHES
EG. 128" LONG TUBE: D6005-128

- 2) MATERIAL: 2.750 OD x 0.375 WALL 7075-T6/T6511 (WW-T-700/7 OR QQ-A-225/9 OR QQ-A-200/11) SEAMLESS ALUMINUM TUBE.
MINIMUM ULTIMATE TENSILE STRENGTH = 77 ksi
MINIMUM YIELD TENSILE STRENGTH = 66 ksi
- 3) TOLERANCES ARE PER ASTM B210 AS FOLLOWS:
O.D.: ± 0.006 MEAN (± 0.012 INCLUDING OVALITY)
WALL: ± 0.015 MEAN (± 0.038 INCLUDING ECCENTRICITY)
LENGTH: XXX $+0.125/-0.000$
STRAIGHTNESS: 0.010" DEVIATION / 12" LENGTH
- 4) EXTREME CARE MUST BE TAKEN TO PROTECT THE OUTSIDE SURFACE OF THE TUBE. THE OUTSIDE SURFACE MUST BE SMOOTH AND FREE FROM SURFACE DEFECTS SUCH AS SCRATCHES, NICKS, OR DENTS. DEFECTS UP TO 0.005" MAY BE BLENDED OUT LONGITUDINALLY. CIRCUMFERENTIAL GRIND MARKS ARE UNACCEPTABLE.
- 5) CHEMICAL CONVERSION COAT PER DART QSI 005 4.1

Copyright © 2000 by DART AEROSPACE LTD

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.